

# MAXHUB

## UC P20



UC Pro 4K 60fps FTZ Camera with 12x Optical Zoom

### UNPRECEDENTED CLARITY FOR A NEW GENERATION OF VIDEO CONFERENCING.

The MAXHUB 4K 60fps UC P20 is the next-generation of video conferencing equipment. This premium 4K UHD camera ensures crystal-clear video in any environment. 12x optical plus 16x digital zoom guarantees sensational clarity with smooth and ultra-silent PTZ. With versatile outputs and plug-and-play simplicity, the UC P20 sets new standards for mid-to-large meeting rooms.

### Ultra-silent PTZ Operation with Versatile Wide Viewing Angles

Tilt 30° Pan 170° | Whisper-silent motor | Up to 255 presets



- HFoV 71° viewing angles combined with smooth pan and tilt control puts every meeting in incredible focus. Whisper-silent motor allows users to adjust angles and zoom performance without pulling attention away from the conversation. Choose from up to 255 preset camera positions to instantly find the angle that's right for you.

### 12x Optical Zoom & 16x Digital Zoom for Exceptional Image Quality Anywhere

12x optical zoom | 16x digital zoom



12x OPTICAL ZOOM



- 12x optical zoom delivers sensational 4K resolution without compromising on clarity at any distance. 16x digital zoom provides more accurate close-ups. You can zoom up to 192 times, extending capture reach to as far as 200 metres.

Unmatched ISP with 2D & 3D DNR  
Delivers Crisp, Clear Images

Unmatched image sensor processor | 1/2.5-inch CMOS image sensor | True WDR



After 2D & 3D DNR

Before 2D & 3D DNR



After WDR

Before WDR

Premium ultra-low CMOS image sensors significantly reduce image noise, for crystal-clear pictures anywhere. Pioneering 2D and 3D DNR technology delivers unbeatable image quality even in low-light conditions. The result is a signal-noise ratio of  $\geq 55\text{dB}$  and above.

Versatile Outputs  
for Plug-and-Play Simplicity

- ① RJ45 (support PoE)    ② HDMI 2.0    ③ USB 3.0

Enjoy an easy set-up with plug-and-play functionality. Multiple ports including HDMI 2.0 and USB 3.0 deliver 4K at up to 60fps, so you can start conferences instantly. You'll be ready for any meeting in seconds, and the camera works with virtually any meeting application.

All Ready for Remote Access

IR remoter | Support for RS232/RS485

Pan, tilt and zoom to find the angle that suits you. A handy compact remote means that you can control your view with ease. RS232/RS485 ports enable quick connectivity with remote control software.



Specification

<b>Camera</b>			
VideoSystem	4K@60fps, 4K@50fps, 4K@30fps, 4K@25fps, 4K@59.94fps, 4K@29.97fps, 1080P@60fps, 1080P@50fps, 1080P@60fps, 1080P@50fps, 1080P@30fps, 1080P@25fps, 1080P@59.94fps, 1080P@59.94fps, 1080P@29.97fps, 720P@60fps, 720P@59.94fps	Video Format	YUY2: max to 1080P@30fps H.264 AVC: max to 2160P@60fps H.264 SVC: max to 2160P@60fps MJPEG: max to 2160P@30fps
Sensor	1/2.5 inch, CMOS, Max Effective Pixel: 8.51M	USB Audio	Supported
Scanning Mode	Progressive	USB Video Communication Protocol	UVC1.1~1.5
Lens	12x, f=4.4mm ~ 52.8mm, F1.8 ~ F2.6	UVC PTZ	Supported
Digital Zoom	16x	<b>Network</b>	
Minimum Illumination	0.5 Lux @ (F1.8, AGC ON)	Video Compression	H.264 / H.265 / MJPEG
Shutter	1/30s ~ 1/10000s	Video Stream	First Stream, Second Stream
White Balance	Auto, Indoor, Outdoor, OnePush, Manual, VAR	First Stream Resolution	3840x2160, 1920x1080, 1280x720, 1024x576, 960x540, 640x480, 640x360
Backlight Compensation	Supported	Second Stream Resolution	1280x720, 1024x576, 720x576(50Hz supported), 720x480 (60Hz supported), 720x408, 640x360, 480x270, 320x240, 320x180
Digital Noise Reduction	2D & 3D Digital Noise Reduction	Video Bit Rate	32kbps ~ 51200kbps
Signal Noise Ratio	$\geq 55\text{dB}$	Bit Rate Control	Variable Rate, Fixed Rate
Horizontal Angle of View	71° ~ 8.2°	Frame Rate	50Hz: 1fps ~ 50fps, 60Hz: 1fps ~ 60fps
Vertical Angle of View	42.7° ~ 4.5°	Audio Compression	AAC
Horizontal Rotation Range	$\pm 170^\circ$	Audio Bit Rate	96Kbps, 128Kbps, 256Kbps
Vertical Rotation Range	$\pm 30^\circ$	Protocols	TCP / IP, HTTP, RTSP, RTMP / RTMPS, ONVIF, DHCP, SRT, Multi-cast
Pan Speed Range	1.6°/s ~ 76°/s	<b>Input &amp; Output</b>	
Tilt Speed Range	0.5°/s ~ 15°/s	Network Interface	1xRJ45: 10/100/1000Mbps Adaptive Ethernet Port
H & V Flip	Supported	Communication Interface	1xRS232 IN: 8pin Min DIN, Max Distance: 30m, Protocol: VISCA / Pelco-D / Pelco-P 1xRS485: 3pin phoenix port, Max Distance: 1200m, Protocol: VISCA / Pelco-D / Pelco-P
Image Freeze	Supported	<b>Audio Interface</b>	
Number of Preset	255	1xLINEIN: 3.5mm Audio Interface	1xHDMI: Version 2.0
Preset Accuracy	0.1°	3G-SDI Interface	1x3G-SDI: BNC type, 800mVp-p, 75Ω.A long to SMPTE 424M standard
<b>UVC Features</b>		USB Interface	1xUSB3.0: Up to 4K@60fps compressed video and 1080P original video can be output
Operate System	Windows 7, Windows 8, Windows 10, MacOS X, Linux, Android	Power Jack	JEITA type (DC IN 12V)
Encode Format	YUY2 / H.264 / H.265 / MJPEG	<b>Power &amp; Physical</b>	
		Input Voltage	DC12V
		Current Consumption	1.0A (Max)
		Operating Temperature	-10°C ~ 40°C
		Storage Temperature	-40°C ~ 60°C
		Power Consumption	12W (Max)
		Dimension	238mmx131.8mmx166.35mm
		NetWeight	1.3kg
		<b>Statement</b>	
		Size and weight may vary by configuration and manufacturing process, please refer to the actual product. The product images are for illustrative purposes only and may slightly differ in appearance, color, size, etc. from the actual product. The description, illustrations, etc. in the document may subject to change in accordance with the latest product specification and performance. Should the above-mentioned change in the document become necessary, the document may be updated without written notice.	
		<b>HDMI™</b> HIGH-DEFINITION MULTIMEDIA INTERFACE	
		NOTICE: The terms HDMI and HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of HDMI Licensing LLC in the United States and other countries.	